



KEY FEATURES

Cost-effective fully integrated solution

3 megapixel camera

High-sensitivity GPS receiver

Long life battery for all-day use

Lightweight and compact

COMPACT ASSET MANAGEMENT SOLUTION FOR YOUR ENTIRE WORKFORCE

Arm your crew with the durable, compact field computer that integrates a rich array of functionality, including photo capture and high-yield GPS positioning. The Juno™ SB handheld is the affordable way to maximize the productivity of your entire workforce.

For asset management and inspection applications, the Juno SB handheld is the perfect tool. A photo provides accurate, detailed documentation of the condition of an asset, while the integrated GPS receiver records the asset's location.

Value for large deployments

The Juno SB handheld is an economical solution ideally suited to utility companies, government organizations, and agencies that are looking to equip their entire field workforce while managing strict budgets. A complete range of cost-effective price points are available that combine the Juno SB handheld with your required field application software.

While minimizing expenditure, you won't have to compromise on features or functionality. The Juno SB handheld includes a 533 MHz processor, 3.5 inch display, and a 3 megapixel camera. Now each member of your workforce has the ability to augment their GPS information with photographs while performing GIS data collection, maintenance, and inspection activities.

Standard wireless capabilities include built-in Bluetooth®, giving you cable-free connections to peripherals such as RFID readers and barcode scanners, and wireless LAN that enables you to access your organization's secure network to get the latest data. No matter what your set-up, the Juno SB handheld gives you flexible connectivity methods to meet your business needs.

The ultimate in mobility

The Juno SB handheld is designed to keep your workforce mobile with the convenience of a single integrated, pocketable device that avoids the need to carry a camera, a GPS data collector, and a PDA.

The long life battery of the Juno SB handheld allows GPS data collection for a full working day, without the need for recharging. The battery is also field-replaceable, for extended periods away from a power source.

You never have to worry about running out of memory in the field with the Juno SB handheld's microSD card slot. Compatibility with high capacity microSD cards provides ample storage for large applications, data and raster background maps, or even entire projects.

Productivity for field and office

In applications such as natural resources and mobile enterprise, where positional accuracy is less important, and high productivity is essential, the Juno SB handheld is ideal. Incorporating a high-sensitivity GPS receiver, it is specifically designed to maximize yield of positions in hostile environments, such as under forest canopy and up against buildings.

If you need 2 to 5 meter accuracy in the field, you can use the integrated SBAS receiver for real-time corrections. Or you can collect GPS data in the field and postprocess it back in the office to ensure positions achieve the required accuracy level for your GIS, and to control the overall quality and consistency of your data.

As part of the Trimble® family of GPS solutions, the Juno SB handheld is fully compatible with Trimble's entire range of Mapping & GIS software, giving you a choice of field-proven software solutions for professional GIS data collection and maintenance. You can easily deploy the Juno SB handheld alongside your current Trimble equipment, and maintain the same workflows and policies.

The Juno SB handheld's Windows Mobile® 6.1 operating system includes personal productivity tools such as Word Mobile, Excel® Mobile, Internet Explorer® Mobile, and Outlook® Mobile, allowing a seamless exchange of data between the field and office.

The lightweight heavyweight

Equip each of your field workers with the durable, lightweight field computer that really packs a punch. The Juno SB handheld is the one tool your mobile workforce can't afford to be without.



Juno SB handheld

STANDARD FEATURES

System

- Windows Mobile 6.1 in Chinese, English, French, German, Italian, Japanese, Korean, Portuguese (Brazilian), Russian, or Spanish
- 533 MHz Samsung processor
- Integrated Bluetooth v2.0 wireless technology
- Integrated 802.11b/g wireless LAN
- Integrated digital camera (color, 3 megapixel resolution)
- 128 MB RAM
- 128 MB non-volatile Flash data storage
- microSD (microSDHC compatible) memory card slot
- QVGA display (240 x 320), sunlight-readable color touch screen
- All-day internally rechargeable and removable Li-Ion battery
- Integrated speaker and microphone
- Audio jack

GPS

- Integrated high-sensitivity GPS/SBAS¹ receiver and antenna
- 2 to 5 meter accuracy after differential correction (real-time or postprocessed)
- NMEA and SiRF protocol support

Standard Software

- Microsoft Office Mobile, includes Excel Mobile, Word Mobile, Internet Explorer Mobile, Outlook Mobile, and PowerPoint® Mobile
- Adobe Reader
- Transcriber (handwriting recognition)

Standard Accessories

- AC Power supply with international adapter kit
- USB data cable
- Stylus (2-pack)
- Wrist lanyard
- Rechargeable Li-ion battery
- Quick Start Guide
- Getting Started CD, containing User Guide

OPTIONAL FEATURES

Optional Software

- TerraSync™ software
- Trimble GPSCorrect™ extension for ESRI ArcPad software
- GPS Pathfinder® Tools Software Development Kit (SDK)
- GPS Pathfinder Office software
- Trimble GPS Analyst™ extension for ESRI ArcGIS Desktop software
- GPS Controller software for controlling NMEA output and in-field mission planning

Optional Accessories

- Vehicle power adapter
- Vehicle mount for windshield or dash
- External GPS patch antenna
- Protective OtterBox Defender Series case with belt clip
- Anti-glare screen protectors (2-pack)
- Clear screen protectors (2-pack)
- Replacement AC Power supply with international adapter kit
- Replacement Li-Ion battery
- Replacement Stylus (2-pack)

© 2008-2009, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and GPS Pathfinder are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. GPS Analyst, GPSCorrect, Juno, and TerraSync are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. Excel, Internet Explorer, Microsoft, Outlook, Powerpoint, and Windows Mobile are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners. Aerial Photography © The GeoInformation Group, 2002-2008. PN 022501-185A (01/09)

TECHNICAL SPECIFICATIONS

Physical

Size	12.9 cm x 7.4 cm x 3.0 cm (5.1 in x 2.9 in x 1.2 in)
Weight	0.23 kg (0.52 lb) with battery
Processor	533 MHz Samsung S3C2443 processor
Memory	128 MB RAM and 128 MB internal Flash storage
Battery	Internal 2600 mAh lithium-ion, rechargeable in unit Power ²
	Low (no GPS, backlight ON ³) 14 hours
	Normal (with GPS and backlight ON) 8 hours

Environmental

Temperature	
Operating	0 °C to +60 °C (32 °F to 140 °F)
Storage	-20 °C to +70 °C (-4 °F to 158 °F)
Drop	76 cm (2.5 ft) drop
	2 drops per 6 sides at ambient temperature 23 °C (73 °F)
Tumble	50 cycles (100 drops) x 50 cm (1.64 ft), 5 cycles/minute

Input/output

Expansion	microSD Card slot (microSDHC compatible)
Display	8.9 cm (3.5 in) QVGA (240 x 320 pixel) TFT
	16 bit (65,536) colors, LED backlight
Interface	Touch screen, hardware control keys, power status LED
	Audio system events, warnings, and notifications
	Soft Input Panel (SIP) virtual keyboard and handwriting recognition software
Audio	Microphone and speaker, record and playback utilities
	Industry-standard 3.5 mm stereo earphone jack
I/O	USB client v2.0 compliant
Radios	Bluetooth 2.0 ⁴ , Wireless LAN 802.11b/g
Digital Camera	3 megapixel color camera with autofocus
	JPEG photo format, WMV video format

GPS

Channels	12 (L1 code only)
Integrated real-time	SBAS ¹
Update rate1 Hz
Time to first fix	30 seconds (typical)
Protocols	SiRF, NMEA-0183

Accuracy (HRMS)⁵ after differential correction

Code Postprocessed	2-5 m
Real-time (SBAS ¹)	2-5 m

¹ SBAS (Satellite Based Augmentation System). Includes WAAS (Wide Area Augmentation System) available in North America only, EGNOS (European Geostationary Navigation Overlay System) available in Europe only, and MSAS available in Japan only.

² Using wireless technology, such as Bluetooth or wireless LAN will consume additional battery power.

³ Backlight setting at 70% brightness.

⁴ Bluetooth and wireless LAN type approvals are country specific. Juno series handhelds have Bluetooth and wireless LAN approval in the USA and EU. For other countries please consult your local Reseller.

⁵ Horizontal Root Mean Squared accuracy. Requires data to be collected using vertical mounting, minimum of 4 satellites, PDOP mask at 99, SNR mask at 12 dBHz, elevation mask at 5 degrees, and reasonable multipath conditions. Ionospheric conditions, multipath signals or obstruction of the sky by buildings or heavy tree canopy may degrade precision by interfering with signal reception. Accuracy varies with proximity to base station by +1 ppm for postprocessing and real-time.

Specifications subject to change without notice.



YOUR LOCAL TRIMBLE OFFICE OR REPRESENTATIVE

NORTH & SOUTH AMERICA

Trimble Navigation Limited
10355 Westmoor Drive
Suite #100
Westminster, CO 80021
USA
+1-720-587-4574 Phone
+1-720-587-4878 Fax

EUROPE & AFRICA

Trimble GmbH
Am Prime Parc 11
65479 Raunheim
GERMANY
+49-6142-2100-0 Phone
+49-6142-2100-550 Fax

ASIA-PACIFIC & MIDDLE EAST

Trimble Navigation
Singapore PTE Limited
80 Marine Parade Road
#22-06 Parkway Parade
Singapore, 449269
SINGAPORE
+65-6348-2212 Phone
+65-6348-2232 Fax



www.trimble.com
store.trimble.com