



KEY FEATURES

High-performance submeter GPS with integrated SBAS and EVEREST multipath technology

Microsoft Windows Mobile 5.0 software, allowing maximum flexibility in software choice

512 MB onboard memory plus removable SD memory

Bluetooth and wireless LAN connectivity options

Rugged handheld with all-day battery

TrimPix technology for wireless camera support



THE TOTAL GPS PLATFORM FOR ALL YOUR GIS FIELD REQUIREMENTS

The GeoXT™ handheld, from Trimble's GeoExplorer® series, is the essential tool for maintaining your GIS. A high performance, submeter GPS receiver combined with a rugged handheld computer, the GeoXT handheld is ideal for use by utility companies, local government organizations, federal agencies, or anyone managing assets or mapping critical infrastructure who needs accurate data to do the job right—the first time.

Delivering consistent submeter accuracy both real-time and postprocessed, the GeoXT handheld is the most dependable submeter solution available. And it's specifically designed with your GIS in mind.

Real-world submeter performance

The GeoXT handheld is optimized to provide the reliable, high-accuracy location data when and where you need it. With advanced features like EVEREST™ multipath rejection technology, the GeoXT handheld outputs quality GPS positions even under canopy, in urban canyons, and in all the everyday environments you work in.

If you need submeter accuracy in real time, you can use corrections from a satellite-based augmentation system (SBAS) like WAAS or EGNOS, or use the integrated Bluetooth® radio to connect to a Trimble® GeoBeacon™ receiver. And if you need that extra edge in precision, you can collect data with Trimble TerraSync™ software or the GPScorrect™ extension for ESRI ArcPad software, and then postprocess back in the office.

Software to fit your workflow

The GeoXT handheld comes with a powerful 416 MHz processor powered by Microsoft® Windows Mobile® version 5.0 software. Windows Mobile software is the industry standard open platform for mobile devices, so you can choose a software solution to match your workflow, whether off-the-shelf or purpose built.

Windows Mobile 5.0 features familiar Microsoft software, including Word Mobile, Excel Mobile, and Outlook® Mobile, giving you all the tools you need for a seamless exchange of data between the field and the office.

Built for the field

The GeoXT handheld has an integrated battery, good for a full day's work; simply charge the battery overnight and you're ready to go again. The GeoXT handheld will last the distance, and its rugged design can take a lot of punishment. Rain, hail, or shine, it's built to keep working, whatever the weather throws at you.

Convenient connectivity

With the GeoXT handheld you have the flexibility to work exactly the way you want to. Do you need to access the Internet or your organization's secure network to get the most up-to-date data? No problem—with the GeoXT handheld you have built-in wireless LAN and Bluetooth technology to ensure you stay connected.

Using the built-in wireless LAN and TrimPix™ technology, the GeoXT handheld can connect to a range of WiFi-capable Nikon digital cameras for automated capture of digital images. Download the TrimPix software and you have an ideal solution for easily collecting high resolution digital photos to link to your GPS positions.

All the memory you need

There's plenty of storage space in the GeoXT handheld for all your GIS data, and with its fast processor even big graphics files load quickly. Because the GeoXT handheld runs Windows Mobile 5.0 software, all your data and applications are stored in persistent memory, so your data is completely safe. And with a Secure Digital (SD) memory card slot, you can add gigabytes of memory for all your map data.

Accuracy you can rely on

Accurate information is crucial to making informed decisions and improving the way you do business. The GeoXT delivers consistent submeter accuracy both real-time and postprocessed, so you know your GIS has the information that others can depend on to do the job right—this time, next time and every time.

STANDARD FEATURES

System

- Microsoft Windows Mobile 5.0 software
- 416 MHz Intel X-Scale processor
- 512 MB non-volatile Flash data storage
- Sealed SD card slot
- Outdoor color display
- Ergonomic cable-free handheld
- Rugged and water-resistant design
- All-day internally rechargeable battery
- Bluetooth wireless
- 802.11b wireless LAN

GPS

- Submeter accuracy in real-time
- Integrated SBAS¹
- RTCM real-time correction support
- NMEA and TSIP protocol support
- EVEREST multipath rejection technology

Software

- GPS Controller for control of integrated GPS and in-field mission planning
- GPS Connector for connecting integrated GPS to external ports
- Microsoft ActiveSync®, Calculator, File Explorer, Internet Explorer, Pictures, Excel Mobile, Outlook® Mobile (Inbox, Calendar, Contacts, Notes, Tasks), Word Mobile, Windows® Media Player
- Transcriber (handwriting recognition)
- Trimble Navigator Sample Application software
- TrimPix software for wireless camera support. Download from www.trimble.com/trimpix.asp

Accessories

- Support module with power supply and USB data cable
- Getting Started Guide
- Getting Started Disc
- Hand strap
- Pouch
- Stylus kit

OPTIONAL FEATURES

Software

- TerraSync software
- Trimble GPScorrect extension for ESRI ArcPad software
- GPS Pathfinder® Tools Software Development Kit (SDK)
- GPS Pathfinder Office software
- Trimble GPS Analyst™ extension for ESRI ArcGIS software

Accessories

- Serial clip for field data and power input
- Vehicle power adaptor²
- Portable power kit²
- Hurricane antenna kit
- External patch antenna
- Pole-mountable ground plane
- Baseball cap with patch antenna pocket
- GeoBeacon receiver
- Hard carry case
- Null modem cable²
- Backpack kit
- 2 meter range pole
- Range pole bracket

© 2002–2007, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, GeoExplorer, and GPS Pathfinder are trademarks of Trimble Navigation Limited, registered in the United States Patent and Trademark Office and in other countries. EVEREST, GeoBeacon, GeoXT, GPS Analyst, GPScorrect, TerraSync, and TrimPix are trademarks of Trimble Navigation Limited. ActiveSync, Microsoft, Outlook, Windows, and Windows Mobile are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. TID13305K (03/07)

TECHNICAL SPECIFICATIONS

Physical

Size	21.5 cm × 9.9 cm × 7.7 cm (8.5 in × 3.9 in × 3.0 in)
Weight	0.78 kg (1.76 lb) with battery
Processor	416 MHz Intel PXA-270 X-Scale processor
Memory	64 MB RAM and 512 MB internal Flash disk
Power	
Low (no GPS or backlight)	1.5 Watts
Normal (with GPS and backlight)	2.7 Watts
High (with GPS, backlight, Bluetooth, and wireless LAN)	3.7 Watts ³
Battery	Internal 6800 mAh lithium-ion, rechargeable in unit 25 Watt-hours

Environmental

Temperature	
Operating	–10 °C to +50 °C (14 °F to 122 °F)
Storage	–20 °C to +70 °C (–4 °F to 158 °F)
Casing	Wind-driven rain and dust-resistant per IP 54 standard Slip-resistant grip, shock and vibration resistant

Input/output

Communications	Bluetooth ⁴ , 802.11b wireless LAN USB client v1.1 compliant ⁵ via support module Serial via optional DE9 serial clip adaptor Ethernet 10/100 BaseT compatible via support module
Bluetooth Profiles	
Client and host support	Serial Port, Object Push
Client support only	Dial-Up Networking
Host support only	File Transfer (using OBEX)
Display	Advanced outdoor TFT, 240 × 320 pixel 65,536 colors, with backlight
Audio	Microphone and speaker, record and playback utilities
Interface	Touch screen, Soft Input Panel (SIP) virtual keyboard 11 hardware control keys, handwriting recognition software Audio system events, warnings, and notifications

GPS

Channels	12 (L1 code and carrier)
Integrated real-time	SBAS ¹
Update rate	1 Hz
Time to first fix	30 seconds (typical)
Protocols	TSIP, NMEA (GGA, VTG, GLL, GSA, ZDA, GSV, RMC)

Accuracy (HRMS)⁶ after differential correction

Code postprocessed	Submeter
Carrier postprocessed ⁷	
With 5 minutes tracking satellites	30 cm
With 10 minutes tracking satellites	20 cm
With 20 minutes tracking satellites	10 cm
With 45 minutes tracking satellites	1 cm
Real-time (SBAS ¹ or external RTCM source)	Submeter

¹ SBAS (Satellite Based Augmentation System). Includes WAAS (Wide Area Augmentation System) available in North America only. And EGNOS (European Geostationary Navigation Overlay System) available in Europe only.

² Serial clip also required.

³ Power draw will vary depending on radio usage.

⁴ Bluetooth and wireless LAN type approvals are country specific. GeoExplorer 2005 series handhelds have Bluetooth and wireless LAN approval in the U.S. and EU. For other countries please consult your local Reseller.

⁵ Fully compatible with USB v2.0 computers.

⁶ Horizontal Root Mean Squared accuracy. Requires data to be collected with minimum of 4 satellites, maximum PDOP of 6, minimum SNR of 39 dBHz, minimum elevation of 15 degrees, and reasonable multipath conditions. Ionospheric conditions, multipath signals or obstruction of the sky by buildings or heavy tree canopy may degrade precision by interfering with signal reception. Accuracy varies with proximity to base station by +1 ppm for postprocessing and real-time.

⁷ Accuracy varies with proximity to base station by +5 ppm.

Specifications subject to change without notice.



NORTH & SOUTH AMERICA

Trimble Navigation Limited
10355 Westmoor Drive
Suite #100
Westminster, CO 80021
USA
+1-720-587-4574 Phone
+1-720-587-4878 Fax

EUROPE, AFRICA & MIDDLE EAST

Trimble GmbH
Am Prime Parc 11
65479 Raunheim
GERMANY
+49-6142-2100-0 Phone
+49-6142-2100-550 Fax

ASIA-PACIFIC

Trimble Navigation
Singapore PTE Limited
80 Marine Parade Road
#22-06 Parkway Parade
Singapore, 449269
SINGAPORE
+65-6348-2212 Phone
+65-6348-2232 Fax